



## Lafil 100 - 120 Lafil 100 - 120 Vario




mm	L	Ø
Lafil 100	100	54
Lafil 120	120	65

Lafil 100, 3 x (3,5 - 3 - 2,5 mm)  
Lafil 120, 3 x (4 - 3,5 - 3 mm)



mm	L	Ø	⌀
Lafil 100	100	54	4,5 ÷ 0,85
Lafil 120	120	65	6,7 ÷ 0,85

\*Roulette incluse  
\*Roulette included



mm	L	P	H
Lafil 100	720	370	1270
Lafil 120	960	360	1260

## Laminatoio doppio a velocità fissa e variabile Fixed and Variable Speeds Double Rolling Mill



	um	LAFIL velocità fissa fixed speed		LAFIL Vario velocità variabile variable speed	
modello / model articolo / item		Lafil 100 (L246200)	Lafil 120 (L252100)	Lafil 100 (L247200)	Lafil 120 (L253200)
Larghezza dei cilindri Rolls width	mm	100	120	100	120
Diametro dei cilindri Rolls diameter	mm	54	65	54	65
Max. apertura cilindri Max. rolls opening	mm	14	16	14	16
Velocità di laminazione Rolling speed	m/min	3,0	3,5	0÷4,5	0÷5,5
Coppia max di laminazione Max. rolling torque	kgm	50	82	50	82
Sforzo max di laminazione Max. rolling pressure	ton	12	18	12	18
Potenza motore Motor power	kW	0,9	1,5	0,9	1,5
Tensione Voltage	v Hz	230/400~3 50/60	230/400~3 50/60	230/400~3 50/60	230/400~3 50/60
Peso Weight	Kg	180	240	183	243

\* lubrificazione olio automatico / automatic oil lubrication  
altre tensioni fornibili su richiesta / other voltages available on request

Cilindri di ricambio Spare part cylinders	Lafil 100	Lafil 120	Lafil 100V	Lafil 120V
- (L) lastra / plate	L246802	L252802	L246802	L252802
- (F) filo / wire	L246803	L252803	L246803	L252803
- roulette	L141802	L252801	L141802	L252801